

UV-S604

UV DTF PRINTER



Self-development



long life



High precision



low cost

TECHNICAL PARAMETER

| | | | |
|-----------------------|---|---|------------|
| Model | UV-S604 | | |
| Printhead | Epson I3200-U1/Epson I1600-U1 | | |
| Printhead Quantity | 3 | | 4 |
| Printing Color | CMYK+W+V | | G+CMYK+W+V |
| Printing Speed | I3200-U1 | 720*1800DPI 6PASS 8m ² /h 720*2400DPI 8PASS 5m ² /h 720*3600DPI 12PASS 4m ² /h | |
| Printing Size | 600mm | | |
| RIP Software | RIIN/Flexiprint/CADlink/Maintop | | |
| Media Transfer | UV AB film | | |
| Lamination | Integrated automatic laminator | | |
| Ink curing | Water cooler+UV LED lamp (to ensure long-term high-intensity operation) | | |
| Power Supply | 220V 50~60HZ 2000W | | |
| Work Environment | Temperature:20°C~30°C Humidity:35%~65% | | |
| Machine size/weight | 1785*864*1590.2mm 270kg | | |
| Packaging Size/weight | 2360*860*860mm 289kg | | |



G+CMYK+W+V



Anti-collision system



HIWIN guide rail



Laminating device